



Wall saw WSE1217

Cutting depths up to 520 mm



Innovative, powerful and low-maintenance electric motor without transmission



Optimised remote control for greater mobility and increased safety



Lightweight control unit enables use in the 16 and 32 A range

The WSE1217 wall saw has been developed for universal applications and everyday use on the construction site. The pioneering P2® drive concept enables the combination of extreme reliability and optimum performance with low service requirements and reduced service costs. The control and main motor represent the entry

level into the exclusive world of TYROLIT Hydrostress modularity with 4 application options by means of an expandable system: wall sawing/wire sawing/circular wire sawing/drilling. The lightweight and compact system components turn assembly and disassembly into child's play.



System & Accessories



Technical data

Saw blade	
Max. cutting depth	520 mm
Max. saw blade Ø	1 200 mm
Free detachable up to Ø	825 mm
Blade flange mounting	Quick-release flange
Saw blade fixing (flush cuts)	6 countersunk head screws, 130 mm graduated circle

Electric motor

Water-cooled high-frequency motor without gearbox	
Output at 16 A	8 kW
Output at 32 A	17 kW

Control unit

Voltage	400 V
Frequency	50/60 Hz
Weight	22 kg

Weight

Wall saw WSE1217 incl. feed motors	22 kg
Electric main drive motor WSE1217	15 kg

System & Accessories

Wall saw system WSE1217	
10989000	Wall saw WSE1217 incl. feed motors
10988900	Electric main drive motor WSE1217 400 V / 50 Hz
10989300	Electric control unit WSE1217 400 V / 50 Hz incl. radio remote control
10981719	Transport trolley
10984100	Blade guard 1 000 mm 3 pcs. AIO
10982079	VAS G Track 1 100 mm alu
10981818	VAS G Track 2 200 mm alu
977523	Track connector for VAS and VS tracks
965987	V-Track feet alu, flat
965987	V-Track feet alu, flat
965987	V-Track feet alu, flat
10980346	Tool box

Accessories

977523	Track connector for VAS and VS tracks
10977882	Blade flange ST compl.
10984099	Blade guard 800 mm 3 pcs. AIO
10984100	Blade guard 1 000 mm 3 pcs. AIO
10984101	Blade guard 1 200 mm 3 pcs. AIO
965987	V-Track feet alu, flat
961983	V-Swivel track feet
10977452	V-Rotary rail support compl.