

Grinding wheels - Rough grinding wheels



PREMIUM 2-in-1 rough grinding wheels

for steel and stainless steel



Application



- + For demanding applications on different steel and stainless steel grades

We recommend

- + 4 mm thickness for peripheral grinding
- + 6 and 7 mm thickness for rough grinding
- + 8 mm thickness for rough grinding with enhanced lifetime

Advantage

- + Bond with coarse grain and a new layer composition enables quick and convenient use with minimal exertion
- + Comfort Start ensures a comfortable start when grinding and increases the level of working comfort
- + Maximum abrasiveness and lifetime

Form	Type number	Dimension	Specification	PU	
 	27	5270	75 x 6 x 9,5	A 30 Q- BFX	10 Pcs.
	34046119	100 x 6 x 16	A 24 Q- BFX	10 Pcs.	
	5287	115 x 4 x 22,23	A 30 Q- BFX	10 Pcs.	
	34046120	115 x 7 x 22,23	A 24 Q- BFX	10 Pcs.	
	5308	125 x 4 x 22,23	A 30 Q- BFX	10 Pcs.	
	34046131	125 x 7 x 22,23	A 24 Q- BFX	10 Pcs.	
	734378	150 x 4 x 22,23	A 30 Q- BFX	10 Pcs.	
	34046132	150 x 7 x 22,23	A 24 Q- BFX	10 Pcs.	
	5349	178 x 4 x 22,23	A 30 Q- BFX	10 Pcs.	
	34046133	178 x 7 x 22,23	A 24 Q- BFX	10 Pcs.	
	34046135	178 x 8 x 22,23	A 24 Q- BFX	10 Pcs.	
	5406	230 x 4 x 22,23	A 30 Q- BFX	10 Pcs.	
	34046134	230 x 7 x 22,23	A 24 Q- BFX	10 Pcs.	
	34046136	230 x 8 x 22,23	A 24 Q- BFX	10 Pcs.	