

Flexible Abrasives - Quick-Change



PREMIUM ZA-P48 PE X Y Quick-Change discs

for stainless steel and aluminum



Application




- + For applications with high stock removal and processing speed (removal of small burrs, welding spots and projections)

We recommend

- + System R with external thread: The larger adhesive surface leads to greater resistance against mechanical stress in comparison to system S
- + Grit size 36/40/50/60 for maximum stock removal
- + Grit size 80/120 for fine grinding

Advantage

- + High viscosity of zirconium leads to improved resistivity
- + Additional layer has a cooling effect and prevents discolorations on the workpiece
- + Perfectly suited for small and hard-to-reach areas
- + Increased stock removal rate
- + Long lifetime and high edge stability due to robust design

Form	Type number	Dimension	Grain	Max RPM	PU	
  	QDISC-PE	34593690	25 x R	60	30000	100 Pcs.
	34593696	38 x R	60	25000	100 Pcs.	
	34593698	38 x R	120	25000	100 Pcs.	
	34593699	51 x R	36	25000	100 Pcs.	
	34593700	51 x R	40	25000	100 Pcs.	
	34593701	51 x R	50	25000	100 Pcs.	
	34593702	51 x R	60	25000	100 Pcs.	
	34593703	51 x R	80	25000	100 Pcs.	
	34593704	51 x R	120	25000	100 Pcs.	
	34593705	76 x R	36	20000	50 Pcs.	
	34593706	76 x R	40	20000	50 Pcs.	
	34593707	76 x R	50	20000	50 Pcs.	
	34593708	76 x R	60	20000	50 Pcs.	
	34593709	76 x R	80	20000	50 Pcs.	
	34593710	76 x R	120	20000	50 Pcs.	