

# Flexible Abrasives - Quick-Change



## PREMIUM CA-P92 PE X Y Quick-Change discs

for stainless steel, high-alloy steels, aluminum



### Application

- + For applications with high stock removal and processing speed (removal of small burrs, welding spots and projections)

### We recommend

- + System R with external thread: The larger adhesive surface leads to greater resistance against mechanical stress in comparison to system S.
- + Grit size 36/40/50/60 for maximum stock removal
- + Grit size 80/120 for fine grinding

### Advantage

- + Excellent lifetime, cutting ability and edge stability
- + Additional layer has a cooling effect and prevents discolorations on the workpiece
- + Perfectly suited for small and hard-to-reach areas
- + Maximum stock removal in a short time

Form	Type number	Dimension	Grain	Max RPM	PU	
	QDISC-PE	34593711	25 x R	36	30000	100 Pcs.
		34593713	25 x R	50	30000	100 Pcs.
		34593714	25 x R	60	30000	100 Pcs.
		34593715	25 x R	80	30000	100 Pcs.
		34594041	25 x S	36	30000	100 Pcs.
		34593720	38 x R	60	25000	100 Pcs.
		34593721	38 x R	80	25000	100 Pcs.
		34593722	38 x R	120	25000	100 Pcs.
		34594052	38 x S	120	25000	100 Pcs.
		34593723	51 x R	36	25000	100 Pcs.
		34593724	51 x R	40	25000	100 Pcs.
		34593726	51 x R	60	25000	100 Pcs.
		34593727	51 x R	80	25000	100 Pcs.
		34593728	51 x R	120	25000	100 Pcs.
		34594057	51 x S	60	25000	100 Pcs.
		34594058	51 x S	80	25000	100 Pcs.
		34594059	51 x S	120	25000	100 Pcs.
		34593729	76 x R	36	20000	50 Pcs.
		34593731	76 x R	50	20000	50 Pcs.
		34593732	76 x R	60	20000	50 Pcs.
	34593733	76 x R	80	20000	50 Pcs.	