

Mounted points - Mounted points



PREMIUM resin-bonded mounted points

for stainless steel



Application


- + For work such as deburring, bevelling and edge breaking on different stainless steel grades

We recommend

- + Grit size 36 for rough grinding
- + Note operating speed of max. 50 m/s

Advantage

- + Resin-mounted points have a vibration reducing effect due to their composition and therefore boast low impact sensitivity
- + Specially suited to stainless steel materials due to their chemically pure bond
- + Particularly suitable for difficult-to-reach places

Form	Type number	Dimension	Specification	PU	
	52ZY	682101	8 x 16 - 6 x 40	A 36 Q4 B0	25 Pcs.
		682103	10 x 20 - 6 x 40	A 36 Q4 B0	25 Pcs.
		34053928	10 x 32 - 6 x 40	A 36 Q4 B0	25 Pcs.
		682104	13 x 25 - 6 x 40	A 36 Q4 B0	25 Pcs.
		682105	16 x 32 - 6 x 40	A 36 Q4 B0	25 Pcs.
		682106	20 x 32 - 6 x 40	A 36 Q4 B0	25 Pcs.
		682107	20 x 40 - 6 x 40	A 36 Q4 B0	25 Pcs.
		34053929	25 x 13 - 6 x 40	A 36 Q4 B0	25 Pcs.
		682110	25 x 32 - 6 x 40	A 36 Q4 B0	25 Pcs.
		34053930	32 x 16 - 6 x 40	A 36 Q4 B0	25 Pcs.
		104962	32 x 40 - 6 x 40	A 36 Q4 B0	25 Pcs.
		104968	40 x 10 - 6 x 40	A 36 Q4 B0	25 Pcs.
		682111	40 x 20 - 6 x 40	A 36 Q4 B0	25 Pcs.
		34053942	50 x 13 - 6 x 40	A 36 Q4 B0	25 Pcs.
		682112	50 x 25 - 6 x 40	A 36 Q4 B0	25 Pcs.